




## broachLine BG

PROFILE GRINDING OF BROACHES



3000 × 600 MM [L × D]









## PROFILE GRINDING OF ROUND AND FLAT BROACHES


- High-precision profile grinding machine for tool industry
- Short retooling times between cylindrical and flat work pieces
- Variety of grinding applications of rotationally symmetric parts
- Easy to program through parameter input

FLEXIBLE CONCEPT FOR STRAIGHT AND HELICAL WORK PIECES



## broachLine BG - PROFILE GRINDING OF BROACHES

- Flexible machine for straight and helical broach tools
- Motor spindle with large rpm range for small and large grinding wheels
- Traveling table design for tools up to 200 mm diameter
- Traveling column design for tools up to 600 mm diameter
- Optional swivel head for helical tools
- Siemens 840D Solution Line
- Comprehensive package of software for the grinding of broaching tools
- Additional software available to grind spline shafts, involute splines and hirth serrations
- Two table drive systems: Ball screw or linear motor
- Dressing spindle on the worktable
- Optional measuring probe



Grinding of large broaches



Shell broaches



Helical broaches

TECHNICAL DATA				
broachLine BG (STRAIGHT)	BG1000S-T	BG 2000S-T	BG 2500S-T	BG 3000S-C
Table drive X-axis	KGT*	KGT*	LIM*	LIM*
Distance between centers [mm]	1000	2000	2500	3000
Center height [mm]	280	280	280	400
Work piece diameter [mm]	10-200	10-200	10-200	20-600
Spindle power [kW]	30	30	30	30
Grinding wheel [mm]	40-400×100	40-400×100	40-400×100	40-400×100
broachLine BG (HELICAL)	BG 1000H-T	BG 2000H-T	BG 2500H-T	BG 3000H-C
Swivel angle [°]	± 120	± 120	± 120	± 120

\* KGT = ball screw; LIM = linear motor

## **GET IN TOUCH WITH US TODAY**

TOGETHER WE WILL FIND A SOLUTION FOR YOUR REQUIREMENTS

ELB-SCHLIFF Werkzeugmaschinen GmbH

Phone: +49 6028 408 0 info@elb-schliff.de www.elb-schliff.de