



DDG 450/580

HIGH-PRODUCTION DOUBLE-DISK SURFACE GRINDING













EFFICIENCY IN TOP FORM

- Designed for simultaneous grinding of parallel surfaces on a variety of work pieces
- Easy integration into existing and new production lines
- Compact system with outstanding machine rigidity
- High level of work piece precision with high throughput rates

CONTINUOUS PRECISION FROM THE FIRST TO THE LAST PART






HIGHLIGHTS DDG 450/580


- Vertical grinding spindle arrangement
- Rotary throughfeed grinding
- Cooling lubricant feed through the center of the grinding spindles
- Integrated measurement control
- Linear dressing system with maximum dressing accuracy
- High process stability

- Automatic tool wear compensation for maximum accuracy
- Simple and accurate change of tilting with three tilting points
- Easy adjustment for different work pieces
- Stable cast-iron machine base
- Low space requirements

- Designed for conventional, diamond or CBN grinding wheels
- Siemens PLC Control and Siemens 12" Touch Panel
- Remote maintenance solution RangeCare® via mobile communications or VPN
- Compatible with all standard automation systems



Rotary throughfeed grinding



All process-relevant parameters and the measuring data are clearly displayed



Measuring device for automatic tool wear compensation

TECHNICAL DATA	DDG 450	DDG 580
Grinding wheel diameter [mm]	457	580
Grinding wheel ring width [mm]	178.5	202.5
Drive power per wheel [kW]	22/30	22/30
Peripheral wheel speed [m/s]	18-40	12-45
Machining process	Rotary throughfeed	Rotary throughfeed
Feed sensitivity of grinding wheels [mm]	0.001-0.1	0.001-0.1
Machine dimensions [H×W×D] [mm]	2300 × 2350 × 2560	2300 × 2350 × 2560
Machine weight without switch cabinet [kg]	6700	6700
Transport disc diameter [mm]	900	830
Max. work piece diameter [mm]	80	85

GET IN TOUCH WITH US TODAY

TOGETHER WE WILL FIND A SOLUTION FOR YOUR REQUIREMENTS

LAPMASTER WOLTERS GMBH

Phone: +49 4331 458 0 info@lapmaster-wolters.de www.lapmaster-wolters.de