




MACRO-L

CREEP FEED-, PROFILE-, AND HEDG GRINDING













SIZE MATTERS!

- Small footprint, machine width only approx. 2.4 m [8 ft]
- Optimized rigidity for vibration dampening
- High removal rates
- Dependable part quality

SETTING NEW STANDARDS IN EFFICIENCY AND PRECISION





HIGHLIGHTS MACRO-L

- Compact design
- Maintenance friendly
- Efficient vibration dampening
- High thermal stability
- Water cooled spindle


- Spindles in different power classes available
- Grinding operations in up to five axes
- Stable temperatures during grinding
- Various types CNC controls available (standard: Siemens 840 D sl)
- Integrated wheel management
- Numerous options available



Grinding compartment with clamping fixture



Table dresser with profile roll



Slot grinding configuration

TECHNICAL DATA	MICRON MACRO-L
Dimensions W × H × D [mm]	approx. 2360 × 2350 × 2770 mm / approx. 92.9134" × 92.5196" × 109.0551"
Weight [kg/lbs]	approx. 9000 kg / 19842 lbs
X-travel [mm/inch]	900 mm* / 35.4330"
Y-travel [mm/inch]	approx. 350 mm* / 13.7795″
Z-travel [mm/inch]	approx. 300 mm* / 11.8110"
Spindle power [kW]	11–37
Spindle rpm	3200/4500/16000
Max. wheel diameter [mm/inch]	400 mm* / 15.7480"
Max. wheel width [mm/inch]	150 mm* / 5.9055"

^{*} Maximum wheel diameter and travel can change due to work piece and fixture size

GET IN TOUCH WITH US TODAY

TOGETHER WE WILL FIND A SOLUTION FOR YOUR REQUIREMENTS

LAPMASTER WOLTERS GMBH

Phone: +49 4331 458 0 micron@lapmaster-wolters.de www.lapmaster-wolters.de

03-2018

WE RESERVE THE RIGHT FOR TECHNICAL CHANGES!