




MODEL 15

OPEN FACE / PNEUMATIC LIFT FLAT LAPPING MACHINE







Open face version (left), pneumatic lift version

MEETING TODAY'S PRECISION SURFACING REQUIREMENTS

- Heavy duty base with integrally mounted drive motor, reduction gearbox
- Wrap-around worktable facilitates parts handling
- Three / four conditioning rings with roller yoke and bearing assemblies to facilitate in-process plate flatness control
- Abrasive feed system designed for water or oil based lapping slurries
- Electrical system wired for various voltages
- High torque drive unit with ½ hp/0.37 kW motor and gear reducer

ACHIEVING HIGH STANDARDS OF FLATNESS AND SURFACE FINISH





HIGHLIGHTS MODEL 15

- Heavy duty work table, vertically adjustable
- High density, cast iron serrated lap plate
- Three high density, cast iron serrated conditioning rings
- Three pressure weights
- Three blank workholder discs
- Three felt pads
- Integral abrasive system complete with pump and multi point compound distribution
- Operator panel with start/stop controls, and multiple range digital process timer
- Waste tank

OPTIONAL TOOLING


- Flatness gauge
- Solid stainless steel backing plates
- Composite faced plates
- Solid cast iron lap plate
- Polishing pads

OPTIONAL FEATURES

- Electronic variable speed drive
- Water cooled
- Peristaltic pump
- Optional plates
- Bench / trolley
- Diamond unit



Open face version



Pneumatic lift version

TECHNICAL DATA	MODEL 15			
VERSION	3R OF LAPPING	3R OF POLISHING	3R PL LAPPING	3R OF CLIPPER
Plate O.D. [in/mm]	15/381	15/381	15/381	15/381
Plate I.D. [in/mm]	3.5/89	3.5/89	3.5/89	3.5/89
Ring O.D. [in/mm]	7/178	7/178	7/178	7/178
Ring I.D. [in/mm]	5.5/140	5.5/140	5.5/140	5.5/140
Ring height [in/mm]	1.77 / 45	1.77/45	1.77/45	1.77/45
# of ring positions	3	3	3	3
Pressure plate thickness [in/mm]	1.18/30	1.18/30	-	1.18/30
Pressure plate weight [lbs/kg]	8.4/3.8	8.4/3.8	-	8.4/3.8
Plate RPM	70	70	70	70
Motor [hp/kW]	0.5/0.37	0.5/0.37	0.5/0.37	0.5/0.37
Voltage	110 V 1 Phase 230 V 230 / 380 V, 3 Phase 230 V, 1 Phase 50 / 60 Hz			
Controls	Adjustable	Adjustable	Adjustable	Adjustable
Dimensions (W×D×H) [in/mm]	28.3/720×28.7/730× 17.7/450	28.3/720×28.7/730× 17.7/450	31.5/800×28.3/720× 42.9/1090	31.5/800×28.3/720× 42.9/1090
Weight [lbs/kg] incl. plates	247/112 *	247/112 *	300/136 **	300/136 **

GET IN TOUCH WITH US TODAY

TOGETHER WE WILL FIND A SOLUTION FOR YOUR REQUIREMENTS

LAPMASTER WOLTERS LIMITED

Phone Sales: +44 1752 891 600 sales@lapmaster-wolters.co.uk www.lapmaster-wolters-uk.com

06-2022

WE RESERVE THE RIGHT FOR TECHNICAL CHANGES!